


CHIPPING HAMMERS & CONCRETE BREAKERS



NC-0S • NC-1S • NC-2S • NC-3S CHIPPING HAMMERS

TYPE "H": HEX. SHANK

TYPE "R": ROUND SHANK



NC-0S

	NC-0S	NC-1S	NC-2S	NC-3S
Piston Dia.	20 mm	28.5 mm	28.5 mm	28.5 mm
Piston Stroke	45 mm	26 mm	52 mm	76 mm
Blows/min.	3,000 bpm	3,000 bpm	2,600 bpm	2,300 bpm
Air Consumption	5.84 l/s	9.17 l/s	10.0 l/s	10.0 l/s
Dimensions	246 x 51 x 136 mm	355 x 74 x 150 mm	375 x 74 x 150 mm	420 x 74 x 150 mm
Net Weight	2.6 kg	5.5 kg	6.2 kg	6.5 kg
Air Inlet	3/8"	3/8"	3/8"	3/8"
Hose Dia.	9.5 mm	9.5 mm	9.5 mm	9.5 mm

AA-10A • AA-15A • AA-20S • AA-30S CHIPPING HAMMERS

TYPE "H": HEX. SHANK

TYPE "R": ROUND SHANK



AA-10A

	AA-10A	AA-15A	AA-20S	AA-30S
Piston Dia.	24 mm	24 mm	28 mm	28 mm
Piston Stroke	52 mm	70 mm	55 mm	79 mm
Blows/min.	2,800 bpm	2,200 bpm	2,600 bpm	2,200 bpm
Air Consumption	6.67 l/s	6.67 l/s	8.33 l/s	8.33 l/s
Dimensions	295 x 70 x 180 mm	330 x 70 x 180 mm	315 x 76 x 175 mm	345 x 76 x 175 mm
Net Weight	4.2 kg	4.7 kg	5.7 kg	6.2 kg
Air Inlet	3/8"	3/8"	3/8"	3/8"
Hose Dia.	12.7 mm	12.7 mm	12.7 mm	12.7 mm

CB-10 • CB-20 • CB-30 • CB-35 CONCRETE BREAKERS

TYPE "R": ROUND SHANK




CB-10

	CB-10	CB-20	CB-30	CB-35
Piston Dia.	35 mm	40 mm	45 mm	45 mm
Piston Stroke	102 mm	165 mm	165 mm	200 mm
Blows/min.	1,700 bpm	1,000 bpm	850 bpm	800 bpm
Air Consumption	16.68 l/s	20.01 l/s	23.35 l/s	25.02 l/s
Dimensions	470 x 88 x 316 mm	565 x 93 x 360 mm	595 x 106 x 360 mm	680 x 106 x 360 mm
Net Weight	13.0 kg	21.0 kg	29.0 kg	32.5 kg
Air Inlet	1"	1"	1"	1"
Hose Dia.	19 mm	19 mm	19 mm	19 mm


< SIZE CHART FOR CHISELS >

SHANK

R=Round



H=Hex.



POINT

M= Moil (※Standard)

B= Blank



F= Flat

C= Cutter



TYPE	MODEL NO.	SHANK		POINT				WIDTH W(mm)	SIZE(mm)					
									L	φ 1	φ 2	D	d1	d2
A	NC-0S	R	H	M	B	F	C	40	200	47	30	12.7	20	16
B	NC-1S~NC3S AA-10A~AA-30S	R	H	M	B	F	C	70	250	60	40	17.5	27	20
C	CB-10	R	—	M	—	F	C	75	400	80	—	26	40	28
D	CB-20	R	—	M	—	F	C	75	400	87	—	30	40	30
E	CB-30/CB-35	R	—	M	—	F	C	80	470	87	—	35	45	34