




3/4" IMPACT WRENCHES



KPT-25DC 3/4" sq.drive



COMPOSITE



Bolt Capacity	25 mm
Sq.Drive	19 mm
Working Torque (Max.)	270 - 900 (1,060) Nm
Free Speed	4,300 rpm
Air Consumption	14.5 l/s
Dimensions	237 x 82 x 217 mm
Net Weight	3.6 kg
Air Inlet	3/8"

KPT-25PC 3/4" sq.drive



COMPOSITE



Bolt Capacity	25 mm
Sq.Drive	19 mm
Working Torque (Max.)	280 - 1,170 (1,170) Nm
Free Speed	4,300 rpm
Air Consumption	14.5 l/s
Dimensions	268 x 82 x 217 mm
Net Weight	4.27 kg
Air Inlet	3/8"

KPT-285P 3/4" sq.drive

KPT-285PL (with 6" long anvil)



Bolt Capacity	25 mm
Sq.Drive	19 mm
Working Torque (Max.)	270 - 900 (1,500) Nm
Free Speed	5,500 rpm
Air Consumption	18.54 l/s
Dimensions	220 / 375 x 94 x 230 mm
Net Weight	5.5 / 6.5 kg
Air Inlet	3/8"

KPT-1460 3/4" sq.drive



Bolt Capacity	25 mm
Sq.Drive	19 mm
Working Torque (Max.)	280 - 1,170 (1,290) Nm
Free Speed	4,600 rpm
Air Consumption	16.18 l/s
Dimensions	280 x 98 x 220 mm
Net Weight	5.4 kg
Air Inlet	1/4"

KPT-280P 3/4" sq.drive

KPT-280PL (with 3" long anvil)



Bolt Capacity	28 mm
Sq.Drive	19 mm
Working Torque (Max.)	280 - 950 (1,300) Nm
Free Speed	4,500 rpm
Air Consumption	8.67 l/s
Dimensions	253 / 292 x 203 x 247 mm
Net Weight	6.8 / 7.0 kg
Air Inlet	3/8"

KPT-25P 3/4" sq.drive



Bolt Capacity	25 mm
Sq.Drive	19 mm
Working Torque (Max.)	150 - 1,000 (1,020) Nm
Free Speed	6,500 rpm
Air Consumption	12.3 l/s
Dimensions	230 x 75 x 215 mm
Net Weight	3.9 kg
Air Inlet	3/8"

KPT-191P 3/4" sq.drive

KPT-191PL (with 3" long anvil)



Bolt Capacity	19 mm
Sq.Drive	19 mm
Working Torque (Max.)	220 - 450 (780) Nm
Free Speed	5,900 rpm
Air Consumption	6.65 l/s
Dimensions	241 / 280 x 82 x 221 mm
Net Weight	4.2 / 4.4 kg
Air Inlet	1/4"

KPT-220P 3/4" sq.drive

KPT-220PL (with 6" long anvil)



Bolt Capacity	25 mm
Sq.Drive	19 mm
Working Torque (Max.)	140 - 610 (750) Nm
Free Speed	5,900 rpm
Air Consumption	14.15 l/s
Dimensions	245 / 400 x 78 x 213 mm
Net Weight	4.8 / 5.3 kg
Air Inlet	1/4"

KPT-1460B 3/4" sq.drive




Bolt Capacity	25 mm
Sq.Drive	19 mm
Working Torque (Max.)	150 - 580 (800) Nm
Free Speed	5,300 rpm
Air Consumption	12.33 l/s
Dimensions	215 x 72 x 215 mm
Net Weight	3.6 kg
Air Inlet	1/4"

KPT-229SL 3/4" sq.drive

(with 6" long anvil)

KPT-229S (with 2" short anvil)



Bolt Capacity	25 mm
Sq.Drive	19 mm
Working Torque (Max.)	340 - 750 (930) Nm
Free Speed	4,500 rpm
Air Consumption	10.83 l/s
Dimensions	382 / 497 x 177 x 177 mm
Net Weight	7.0 / 7.5 kg
Air Inlet	3/8"