


3/8" & 1" IMPACT WRENCHES



KPT-12CE 3/8" sq.drive



COMPOSITE



Bolt Capacity	12 mm
Sq.Drive	9.5 mm
Working Torque (Max.)	50 - 270 (310) Nm
Free Speed	7,500 rpm
Air Consumption	11.8 l/s
Dimensions	173 x 60 x 172 mm
Net Weight	1.4 kg
Air Inlet	1/4"

KPT-12DS 3/8" sq.drive



Short!



Bolt Capacity	12 mm
Sq.Drive	9.5 mm
Working Torque (Max.)	32 - 285 (285) Nm
Free Speed	10,000 rpm
Air Consumption	5.83 l/s
Dimensions	142 x 58 x 176 mm
Net Weight	1.4 kg
Air Inlet	1/4"

KPT-12W 3/8" sq.drive



Bolt Capacity	10 mm
Sq.Drive	9.5 mm
Working Torque (Max.)	7 - 90 (120) Nm
Free Speed	12,000 rpm
Air Consumption	8.76 l/s
Dimensions	138 x 52 x 168 mm
Net Weight	1.3 kg
Air Inlet	1/4"

KPT-12BB 3/8" sq.drive



mini



PALM SIZE

Bolt Capacity	10 mm
Sq.Drive	9.5 mm
Working Torque (Max.)	5 - 50 (70) Nm
Free Speed	10,000 rpm
Air Consumption	4.4 l/s
Dimensions	137 x 40 x 47 mm
Net Weight	0.46 kg
Air Inlet	1/4"

KPT-12WX 3/8" sq.drive



Bolt Capacity	10 mm
Sq.Drive	9.5 mm
Working Torque (Max.)	7 - 90 (120) Nm
Free Speed	12,500 rpm
Air Consumption	5.06 l/s
Dimensions	177 x 43 x 86 mm
Net Weight	0.91 kg
Air Inlet	1/4"

KPT-32PC 1" sq.drive



COMPOSITE



Bolt Capacity	32 mm
Sq.Drive	25.4 mm
Working Torque (Max.)	280 - 1,100 (1,150) Nm
Free Speed	4,300 rpm
Air Consumption	14.5 l/s
Dimensions	268 x 82 x 217 mm
Net Weight	4.27 kg
Air Inlet	3/8"

KPT-326P 1" sq.drive



Bolt Capacity	32 mm
Sq.Drive	25.4 mm
Working Torque (Max.)	280 - 1,000 (1,650) Nm
Free Speed	5,500 rpm
Air Consumption	18.54 l/s
Dimensions	220 x 210 x 230 mm
Net Weight	5.5 kg
Air Inlet	3/8"

KPT-385P 1" sq.drive



KPT-385PL (with 8" long anvil)



Bolt Capacity	32 mm
Sq.Drive	25.4 mm
Working Torque (Max.)	200 - 1,350 (2,200) Nm
Free Speed	4,000 rpm
Air Consumption	18.54 l/s
Dimensions	250 / 450 x 199 x 300 mm
Net Weight	9.0 / 10.4 kg
Air Inlet	1/2"

KPT-321P 1" sq.drive

KPT-321PL (with 8" long anvil)



Bolt Capacity	32 mm
Sq.Drive	25.4 mm
Working Torque (Max.)	590 - 1,500 (2,000) Nm
Free Speed	4,300 rpm
Air Consumption	12.83 l/s
Dimensions	266 / 432 x 197 x 280 mm
Net Weight	9.5 / 11.05 kg
Air Inlet	3/8"

KPT-381P 1" sq.drive

KPT-381PL (with 8" long anvil)



Bolt Capacity	38 mm
Sq.Drive	25.4 mm
Working Torque (Max.)	750 - 1,900 (2,500) Nm
Free Speed	4,500 rpm
Air Consumption	11.67 l/s
Dimensions	266 / 432 x 197 x 280 mm
Net Weight	10.3 / 14.3 kg
Air Inlet	3/8"

KPT-452P 1" sq.drive

KPT-452PL (with 9" long anvil)



Bolt Capacity	45 mm
Sq.Drive	25.4 mm
Working Torque (Max.)	1,200 - 2,500 (3,100) Nm
Free Speed	2,900 rpm
Air Consumption	13.33 l/s
Dimensions	322 (510) x 204 x 294 mm
Net Weight	14.2 / 16.2 kg
Air Inlet	3/8"